



Scientific and Technical Gases Ltd
 APV House, Speedwell Road,
 Parkhouse Industrial Estate,
 Newcastle under Lyme, Staffordshire,
 United Kingdom, ST5 7RG

TEL: +44 (0) 1782 566897
 FAX: +44 (0) 1782 564906
 EMAIL: info@stgas.eu
 WEBSITE: www.stgas.eu



**WORLDWIDE
 SUPPLIER OF
 QUALITY GAS
 PRODUCTS
 AND SERVICES**



STG/04/08.10



60DA - 60 LITRE ALUMINIUM NON-REFILLABLE CYLINDER

CONTENTS

60 Litres

SERVICE PRESSURE

34 bar (500psi)

DIMENSIONS

Height 365 mm, Diameter 90 mm

WEIGHT

1.19 Kg

CYLINDER MATERIAL & VALVE

Aluminium - approved to ISO11118
 Connection C10 valve (5/8"-18)

STANDARDS

NPL, UKAS or NIST standards.
 Manufactured gravimetrically
 to ISO 6142

EQUIPMENT

- Cylinder valve compatible with all major manufacturers regulators
- Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
- On-Demand Flow Regulator (ODFR for non-reactive, H₂S and SO₂ mixtures)
- Variflow regulator (non-reactive gases)

WARRANTY

Non-reactive gases	36 months
Ethanol	24 months
H ₂ S, SO ₂ and 4 gas mixtures	12 months
NO, NH ₃ , HCN, ETO	12 months
Cl ₂ (min 5ppm)	9 months
HCl (min 5ppm)	8 months
NO ₂	6 months

MIXTURE TOLERANCES

Minor components are certified to the following analytical tolerance

- 2-20ppm = +/- 10%
- 21- 50ppm = +/- 5%
- 51-300ppm = +/- 2%

